

# WALL PACK LIGHT

Lighting a wonderful life




## Features & Benefits

- ▶ DLC Qualified ETL / DLC Listed
- ▶ IP 65 Rated
- ▶ Long life – High Brightness
- ▶ Uniform And Consistent Color
- ▶ Excellent Thermal Design
- ▶ 15–30 Foot Height Performance
- ▶ 50,000 Hours Rated Life
- ▶ Photocell Sensor Compatible
- ▶ Die-cast Aluminium Housing
- ▶ Borosilicate Glass Lens

## Applications

- ▶ Area Lighting
- ▶ Build Lighting
- ▶ Billboard Lighting
- ▶ Stadium Lighting



Unit: mm

| POWER | L   | W   | H   | NW     | GW     |
|-------|-----|-----|-----|--------|--------|
| 30 W  | 223 | 238 | 226 | 3.1 KG | 3.8 KG |
| 50 W  | 369 | 191 | 228 | 3.3 KG | 3.9 KG |
| 80 W  | 470 | 235 | 228 | 4.0 KG | 4.6 KG |
| 120 W | 470 | 235 | 228 | 4.1 KG | 4.7 KG |



## Product Description

KDCLED traditional wall pack comes in rugged cast-aluminum housing with excellent thermal design. Design Lights Consortium V4.3 qualified, our product offers a popular classic appearance for your needs.

Delivering up to 10,000 lumens by replacing up to 575-watt metal halide luminaires, with energy saving up to 80%. The traditional shape maintains an aesthetic appearance and will replace any building's wall pack or perimeter lighting.

LED Wall Pack Light widely used in carports, loading areas, driveways, parking area and pathways. Designed for wall mounting above four feet from ground.



# WALL PACK LIGHT Applications



## Specifications


| Description | CCT        | Watt | Lumen    | Equip Wattage | Color  | Voltage   | Life Span   |
|-------------|------------|------|----------|---------------|--------|-----------|-------------|
| KF-G-30W    | 3000-5700K | 30   | 4148 lm  | 175W          | Bronze | 100-277 V | >50,000 HRS |
| KF-G-30W    | 3000-5700K | 30   | 3719 lm  | 175W          | Bronze | 200-480 V | >50,000 HRS |
| KF-G-50W    | 3000-5700K | 50   | 6285 lm  | 250W          | Bronze | 120-277 V | >50,000 HRS |
| KF-G-50W    | 3000-5700K | 50   | 5639 lm  | 250W          | Bronze | 200-480 V | >50,000 HRS |
| KF-G-80W    | 3000-5700K | 80   | 9036 lm  | 400W          | Bronze | 120-277 V | >50,000 HRS |
| KF-G-80W    | 3000-5700K | 80   | 8967 lm  | 400W          | Bronze | 200-480 V | >50,000 HRS |
| KF-G-120W   | 3000-5700K | 120  | 13376 lm | 575W          | Bronze | 120-277 V | >50,000 HRS |
| KF-G-120W   | 3000-5700K | 120  | 12993 lm | 575W          | Bronze | 200-480 V | >50,000 HRS |

WALL PACK LIGHT

WALL PACK LIGHT

## Accessories (available for purchase)

### Cut Off Shield



|       |                |                                       |
|-------|----------------|---------------------------------------|
| SD001 | Shield-WP-KF-G | Full Cut-Off Shield for 30,40,80,120W |
|-------|----------------|---------------------------------------|

### Lens



|       |              |            |
|-------|--------------|------------|
| PC001 | LENS-PC-WP-G | PC Lens    |
| GL001 | LENS-GL-WP-G | Glass Lens |

### Photocell



|      |                   |                           |
|------|-------------------|---------------------------|
| P001 | SEN-Photo-WP-KF-G | Button Photocell 100-277V |
|------|-------------------|---------------------------|



## Photometric Data

