

OVERTURE

Overture creates a linear colorized world!

Accent your vacuum canopies, tunnel arches or architectural lines into a fun world of rainbow-liscious goodness.

Questions? Please reach out to info@bigdotlighting.com or call us at (615) 850-1870



Octave RGB LED Light Fixture	DMX-512 Controllable
Chip Type	SMD5050 RGBW LED
Power	80 Watts
Beam Angle	270 Degrees
Input Voltage	AC100-208V
Lamp Size	7.5' x 1" x 6" (whip varies)
Weight	1 LB
Finish Color	White/Transparent
Waterproof Grade	IP68
Power Factor	>.5@120V >0.29 @208V
Life Span	50,000 Hours
Fixture Material	Polyvinyl Chloride
Manufacturer's Warranty	5 Years

Construction & Installation

The linear Overture gen II fixture is constructed from Polyvinyl Chloride and can easily bend to conventional vacuum arches. Within the tube, 22 pixels allowing for multiple colors at once within the fixture!

Installation typically involves 3 c-clamp brackets, a 9' power whip, and 1 driver provided with a bundle purchase.

Electrical & Operations

The Overture fixture is universal voltage (100-208V) with a high quality RGB driver. It can operate in temperatures -20 degrees Celsius to 40 degrees Celsius with high-efficacy LED chips to maintain overall cool fixture temperatures.

DMX-Full Scale RGB Practical Applications

Overture is the perfect way to burst color onto the linear features inside and outside of your facility. With our monthly managed service, we or you can setup your shows 3, 6, and 12 months or further.

www.OctaveLighting.com

